



Product Data

Transcal N Heat transfer oil

Transcal™ N is a high quality mineral oil possessing low vapour-pressure characteristics as well as high levels of thermal stability, specific heat and thermal conductivity.

Transcal N is recommended for non-pressurised, closed liquid-phase heating systems operating at bulk-fluid temperatures up to 320°C, and a maximum film temperature of 340°C.

Such systems are used widely in the food, construction, plastics, timber, oil and gas processing and on ships and where waste heat is extracted from flue gases.

Before being commissioned, the system should be pressure tested for leaks and then thoroughly flushed with Transcal N. Water should never be used. Having been flushed and drained, the system should be filled with fresh Transcal N. Filling is complete when the oil level in the expansion chamber is at 30-45% of the level expected at operating temperature. All air must be completely evacuated from the system before the temperature is raised to operating level. Since mineral oils expand when heated, an expansion chamber must be incorporated in the system. This is the only location where the oil is likely to be in contact with the atmosphere.

Despite the excellent oxidation stability of Transcal N, various precautions must be taken to minimise exposure to air, especially if the temperatures of the fluid in the expansion chamber exceed 50°C. A floating cover can be used or the oil can be blanketed with inert gas.

Note: It is quite normal for the oil temperature to be higher than its flash and fire point in a correctly operated heat transfer system fitted with an inert gas blanket. Under the operating conditions, there should not be a combustion risk hazard with the oil. However, the oil should not be operated above the upper bulk temperature limit of 320°C as recommended above.

- Excellent heat-transfer properties and consistently high heat-transfer performance.
- Ease of circulation even when a system is started from cold.
- Contains all essential characteristics to ensure a long and trouble free service.

Name	Method	Units	Transcal N
Density at 15°C	ASTM D1298	g/ml	0.875
Flash Point, PMCC	ISO 2719, ASTM D93	°C	210
Flash Point, COC	ISO 2592, ASTM D92	°C	221
Fire Point	ISO 2592, ASTM D92	°C	243
Viscosity @ 40°C	ISO 3014, ASTM D445	mm ² /s	31
Viscosity @ 100°C	ISO 3014, ASTM D445	mm ² /s	5.2
Pour Point	ASTM D97	°C	-12
Autogenous-ignition Temperature	ASTM D2155	°C	350
Neutralisation Value	ASTM D974	mgKOH/g	<0.05
Ramsbottom Carbon Residue	ISO 4262, ASTM D524	% wt	<0.05
Coefficient of Thermal Expansion		per °C	0.00077
Normal Operating Range of Bulk Temperatures		°C	-10 to 320

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Transcal N
22 Nov 2012
BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Australia Level 8 (QV1 Building), 250 St. Georges Terrace, Perth WA 6000, Australia. Customer Service Number +61 (0)8 9420 1825, **Dubai** City Tower 2, 6th Floor PO BOX 1699, Sheikh Zayed Road, Dubai, U.A.E. Customer Service Number +971 4 3079304, **Norway** Drammensveien 167, Box 153 Skoyen, 0212 Oslo, Norway. Customer Service Number +47 22 51 12 43 501, **Singapore** Keppel Bay Towers, 1 Harbourfront Avenue 02-01, Singapore 098632, Singapore. Customer Service Number +65 6371 8478, **United Kingdom** BlueSky Business Space, Westpoint House, Pavilion 2 Prospect Park, Prospect Road, Arnhall Business Park, Westhill. AB32 6FJ, UK. Customer Service Number +44 (0)1224 766900, **USA** 501 Westlake Park Boulevard, Houston, Texas 77079, USA. Customer Service Number +1 800 339-7157, **Brazil** de Ulhóia Rodrigues 939, Torre Jacarandá, 7o Andar, Barueri - SP, CEP 06464-040, Brazil. Customer Service Number +55 11 4133 7835

www.castrol.com/industrial

