



Aircol SR Range

Synthetic air compressor lubricant

Description

The Castrol Aircol SR compressor oil range of premium lubricants are designed for use in rotary screw compressors and are based on polyalphaolefin (PAO) fluids

Application

Aircol SR is suitable for use in oil flooded rotary screw compressors and is classified as follows:

- DIN 51506 classification- VDL
- ISO 6743/3-DAG, DAH and DAJ for rotary air compressors

Aircol SR grades meet the requirements of:

- Atlas Copco 8000 hour oil drain interval
- Kaeser

Features and Benefits

- Increased oil service life
- Very low deposit forming tendency, extends service life of filters and separators
- Outstanding oxidation stability and antiwear performance providing long lubricant and equipment life
- Ester-free formulation eliminates the formation of corrosive acids leading to longer equipment life
- High viscosity index gives improved sealing at high discharge temperatures whilst still permitting operation at low ambient temperatures
- Excellent water separation characteristics allow condensation to readily separate from the oil, minimising the risk of emulsions which could block the oil separator element

Technical Data

Name	Method	Units	Aircol SR 32	Aircol SR 46	Aircol SR 68
ISO Viscosity Grade			32	46	68
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	32	46	68
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	6.1	7.8	10.7
Viscosity, Kinematic 0°C	ASTM D445	mm ² /s		437	
Viscosity Index	ASTM D2270		137	137	142
Density @ 15°C, Relative	ASTM D4052	g/ml	0.831	0.837	0.839
Flash Point, COC	ASTM D92	°C	264	264	264
Pour Point	ASTM D97	°C	-54	-54	-54
Rust Test (24hrs, Synthetic Sea Water)	ISO 7210 / IP 135B		Pass	Pass	Pass
RPVOT	ASTM D2272	mins	4500	3000	3000
FZG Gear Test (A/8.3/90)	DIN 51354		8	9	9

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 600C, exposed to hot sun or freezing conditions.

Aircol SR Range

06 Sep 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Australia Level 8 (QV1 Building), 250 St. Georges Terrace, Perth WA 6000, Australia. Customer Service Number +61 (0)8 9420 1854

Dubai City Tower 2, 6th Floor PO BOX 1699, Sheikh Zayed Road, Dubai, U.A.E. Customer Service Number +971 4 3079304

Norway Drammensveien 167, Box 153 Skoyen, 0212 Oslo, Norway. Customer Service Number +47 22 51 12 43

Singapore Keppel Bay Towers, 1 Harbourfront Avenue 02-01, Singapore 098632, Singapore. Customer Service Number +65 6371 8478

United Kingdom BlueSky Business Space, Westpoint House, Pavilion 2 Prospect Park, Prospect Road, Arnhall Business Park, Westhill. AB32 6FJ, UK. Customer Service Number +44 (0)1224 766900

USA 501 Westlake Park Boulevard, Houston, Texas 77079, USA. Customer Service Number +1 800 339-7157

www.castrol.com/offshore

Page 2 of 2

