



APPLICATIONS

Eni Grease CC 3 is a yellow anhydrous-calcium base grease, smooth-textured.

The calcic base gives good water washout resistance characteristics both in presence of hot or cold water.

Eni Grease CC 3 can be applied by automated and manual pressure greaser for the lubrication of pins, bearings, guides and joints also exposed to the moisture, water action and subjected to thermal and mechanical not heavy stresses (speed and pressure).

Is not suitable for use in centralized lubrication systems.

CUSTOMER ADVANTAGES

- Ensures a film on surfaces with good lubricating and protective characteristics
- Water Repellent and insoluble both in hot or cold water

SPECIFICATIONS & APPROVALS

- ISO 12924 L-XBBGA 3
- DIN 51825 K 3G -20





CHARACTERISTICS

Properties	Method	Unit of Measure	Typical
Consistency (NLGI grade)	-	-	3
Thickener type	-	-	calcium anhydrous
Base oil type	-	-	mineral
Base oil viscosity at 40 °C	ASTM D 7042	mm ² /s	100
Appearance	-	-	smooth-textured
Colour	-	-	light amber
Drop point	ASTM D 566	°C	150
Penetration, worked, 60 d. s.	ASTM D 217	dmm	235
Water washout at 79°C	ASTM D 1264	% (m/m)	2
Temperature range	-	°C	-20/+80



eni