

Castrol Inertox Heavy

Fully synthetic high-temperature grease

Description

Castrol Inertox™ Heavy is chemically and thermally one of the most stable lubricants in the Castrol range. Formulated from an advanced synthetic fluid and thickened with a non soap base which is temperature stable and fortified with a blend of additives and lubricating solids for exceptional wear protection.

Application

Inertox Heavy is designed for universal long-term application in anti-friction and plain bearings under hostile ambient conditions. Inert to most corrosive and/or other aggressive media.

For rolling and sliding bearings with extended re-lubrication intervals, high temperatures or under hostile ambient conditions such as in:

- paint drying lines
- film stretching machines
- tenter frames for textiles
- oven carriages in the ceramics industry

For lubrication of seals and friction points inside high vacuum chambers, such as found in the electronics industry. Temperature application range: -25°C/-13°F to +260°C/+500°F (at higher operating temperatures adequate ventilation must be ensured).

Advantages

- Excellent thermal and chemical stability – ensures the grease can operate in adverse applications and is resistant to:
 - hot and cold water, oils, oil-in-water emulsions
 - inorganic and organic acids, alkaline solutions
 - solvents based on hydrocarbons, e.g. naphtha, benzene, toluol, paraffin etc.
 - solvents based on chlorinated hydrocarbons, e.g. trichloroethylene (TRI), perchloroethylene (PER), dichloromethane (methylene chloride) etc.
 - alcohols, ketones (acetone), halogens
 - radioactive radiation (gamma rays)
- High wear protection, excellent lubricating capabilities, good load carrying capacity, outstanding pressure resistance
 - leads to longer bearing life, extended lubrication cycles and uninterrupted service
- Extremely low evaporation loss in vacuum systems- ensures continual lubrication
- Non-flammable – grease can be exposed to extreme conditions ensuring safe use
- Good corrosion protection – helps prevent rust and oxidation on metal surfaces

Typical Characteristics

Test	Method	Units	Inertox Heavy
Appearance, Visual	-	-	White
Thickener Type	-	-	PTFE
Base Oil Type	-	-	PFPE
NLGI Grade	-	-	2
Density @ 20°C/68°F	ASTM D1475	g/ml	1.93
Worked Penetration, 60 strokes @ 25°C/77°F	ISO 2137 ASTM D217	0.1mm	265 - 295
Dropping Point	ISO 2176 ASTM D2265	°C/°F	None
Base Oil Viscosity @ 40°C/104°F	ISO 3104 ASTM D 445	mm ² /s	150 (*)
Corrosion Protection (SKF Emcor)	ISO 11007 ASTM D 6138	Rating	0/0
Water Resistance, 90°C/194°F, 3h	DIN 51807-1	Rating	0
Vapour Pressure Base Fluid @ 20°C/68°F	-	hPa	10 ⁻⁴
DIN Classification	DIN 51502	-	KFK 2 U-25
ISO Classification	ISO 6743/9	-	L-XCGHA-2

Subject to usual manufacturing tolerances.

* Fresh product, at temperatures above 100°C viscosity will increase gradually up to 500 mm²/s.

Additional Information

- Castrol Inertox Heavy should not be mixed with other greases or oils
- Clean the lubrication surfaces thoroughly with e.g. petroleum ether before application

Castrol, Inertox, and the Castrol logo are trademarks of Castrol Limited, used under licence

INTERNATIONAL All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial